



ORWAK COMPACT 3120

The ORWAK COMPACT 3120 is perfect for both cardboard and plastic and offers strong compaction on the spot: compact machine design, yet impressive volume reduction and a bale weight of up to 220 lbs. The loading gate is extra wide, 40"! For rich placement opportunities, the 3120 is a single phase unit.



**EXTRA WIDE
INFEED**



**BALE WEIGHT
CARDBOARD**



ORWAK BENEFITS



MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time for your core activities!

MORE SPACE & ORDER

Our balers rapidly minimize the space the waste takes up, keeping aisles free and tidy.

LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced CO₂ emissions. Sorting at source yields a higher quality of waste material for recycling.

WHY ORWAK COMPACT?

- Strong compaction on the spot! Requires little space, yet provides effective volume reduction
- Easy-to-handle light weight bales
- The best choice for small to medium size volumes of cardboard and plastic



ORWAK COMPACT 3120

Compact and versatile baler

SMART DESIGN

Smart, compact machine design for easy transportation and installation. Generous infeed for easy and convenient loading.

AUTOSTART FOR EFFICIENT COMPACTION

An autostart function allows the baler to start compacting the material as soon as you close the door.

BALE EJECTION

The bales weigh up to 220 lbs and are easily removed thanks to a semi-automatic bale ejection function.

Material selector for cardboard and plastic

Full bale indicator

Service indicator



Adjustable bale size

- User-friendly panel
- Autostart
- Top cover made of recycled plastic
- Adjustable bale height in three sizes



ORWAK COMPACT 3120 IS OPTIMIZED FOR:

PAPER

- Cardboard
- Shredded paper

OTHER METALS

- Steel straps

PLASTIC FOIL

- Shrink film
- Plastic bags

OTHER PLASTICS

- Plastic straps

SILENT OPERATION CONTRIBUTES TO A BETTER WORKING ENVIRONMENT

Thanks to a silent type of hydraulics, the sound emission is low, which contributes to improving the working environment for the employees and is an important feature if the baler is installed close to customers.

ORWAK CONNECT COMMUNICATION


The COMPACT balers are ready to communicate when choosing the option Orwak Connect. It is a modem-based communication service enabling the baler to send updates and alerts to the caretaker as well as vital information and bale statistics to the web portal.

Complies with the EN 16500:2014 safety requirement standard for vertical balers

DIMENSIONS & SPECIFICATIONS

DIMENSIONS

A	B	C	D	TRANSPORT-HEIGHT
7'7"	47"	36"	75"	7'7" (<6'7" on demand)



TECHNICAL SPECIFICATIONS

LOADING APERTURE	CYCLE TIME	PRESS FORCE	BALE SIZE	BALE WEIGHT	MACHINE WEIGHT	NOISE LEVEL	PROTECTION CLASS	OPERATING POWER
Width: 40" Height: 18"	33 secs	HP: 13,230 lbs LP: 8,800 lbs	Width: 40" Depth: 28" Height: 32"	Cardboard: Up to 220 lbs Plastic: Up to 286 lbs	1279 lbs	62.3 db (A)	IP 55	Single Phase 115 V, 60 Hz, 15 A

We reserve the right to make changes to specifications without prior notice. Bale/bag/bin weights are dependent upon material type.

ORWAK NORTH AMERICA, INC.

3125-108 Gresham Lake Road
Raleigh, NC 27615, USA
Phone: +1-800-747-0449
Email: balers@orwakbalers.com

ORWAKBALERS.COM

ORWAK
PART OF Julo GROUP